

B2B TECHNICAL SPECIFICATION & CONTAINER LOADING SHEET · K-BEAUTY TONER PAD SUBSTRATES

K-Beauty Dry Toner Pad Substrates (Die-Cut Rounds & Slit Bobbins)

Dual-Texture 3D Pearl / Plain, 22-Mesh Gauze, Centella Green & Unbleached Cotton · Ø55–Ø80 mm · Essence-Stable Spunlace

Engineered for cosmetic contract fillers (OEM/ODM labs in Korea, USA, Europe & ASEAN) producing pre-soaked PHA/AHA/BHA/Cica toner pads. Available as precision die-cut dry stacks in cleanroom PE barrier bags (ready for jar dosing) or slit master bobbins (width 60–1,600 mm).

1. STANDARD OEM / PRIVATE-LABEL SKU MATRIX & 20GP / 40HQ CONTAINER LOADING

Model	Fiber Substrate	GSM & Weave	Sheet Size	Count	Pack Format	Carton Spec	20GP / 40HQ	OEM MOQ
ZF-TPS01	100% Cotton Dual-Side	65 GSM · Pearl + Plain	Ø 60 mm / Ø 65 mm	1,000 pcs / sterile bag	Cleanroom Double PE Carton	20,000 pcs / ctn (48×38×40 cm)	6.5M / 15.0M pads	100,000 pads
ZF-TPS02	3-Layer Cushion Pulp/Rayon	140 GSM · Waffle/Smooth	Ø 60 mm (U-Cut Opt.)	1,000 pcs / bag	Cleanroom Double PE Carton	12,000 pcs / ctn (50×40×42 cm)	3.8M / 9.0M pads	100,000 pads
ZF-TPS03	22-Mesh Exfoliating Gauze	75 GSM · Cross-Mesh	Ø 60 mm / Ø 70 mm	1,000 pcs / bag	Cleanroom Double PE Carton	18,000 pcs / ctn (48×38×40 cm)	5.8M / 13.5M pads	100,000 pads
ZF-TPS04	Elastic Wet-Pack Substrate	48 GSM · 1:2.2 Stretch	60×70 mm Rounded	1,000 pcs / bag	Cleanroom Double PE Carton	25,000 pcs / ctn (48×38×40 cm)	8.0M / 18.5M pads	100,000 pads
ZF-TPS05	Slit Master Roll (Bobbins)	45–100 GSM Custom	Width 60–320 mm	500–1,000 m / roll	Shrink-Film + Export Pallet	4–8 bobbins / pallet	6,500 kg / 15,500 kg	500 kg / GSM

2. ISO 9073 LABORATORY BENCHMARKS, COMPLIANCE & EXPORT PARAMETERS

Engineering / Quality Parameter	Verified ZEFU Standard	Testing / Compliance Metric	Verified Benchmark & Scope
Acid / Essence Stability	Zero yellowing or fiber breakdown in pH 3.2–8.5 AHA/BHA/Cica	Die-Cut Tolerance	±0.3 mm concentric precision · Zero frayed edge lint
Binder & Chemical Purity	100% Hydroentangled (0% chemical binders, 0% latex)	Bioburden Control	Cleanroom packed · Ready for gamma/autoclave or direct dosing
Liquid Holding Ratio	750%–1,100% essence retention without jar bottom pooling	HS Code & Certs	5603.92 / 5601.21 · OEKO-TEX® Class I · SGS CANWT00472237

3. PRIVATE-LABEL CUSTOMIZATION, SAMPLE POLICY & COMMERCIAL TERMS

Commercial Term	ZEFU Factory Standard	Service Milestone	Guaranteed Execution
Complimentary Swatch Kit	48-Hour DHL/FedEx dispatch (40–100 GSM swatches + 7 patented weaves)	Custom Pre-Production Sample	5–7 Days with your custom printed box/bag dieline
Mass Production Lead Time	7 Days (Stock sizes) · 15–20 Days (Custom printed packaging)	Container Consolidation	Mixed-SKU 20GP (28 CBM) & 40HQ (68 CBM) supported
Trade & Payment Terms	EXW Foshan · FOB Guangzhou/Shenzhen · CIF · DDP (US/EU/AU/KSA/SEA)	Factory Audit & Direct Desk	Intertek CNIR2601SZ10615 · keke@zefumfg.com · +86 139 2512 2895

ZERO-RISK OEM ONBOARDING & 48H FREE SWATCH DISPATCH: Email keke@zefumfg.com or WhatsApp **+86 139 2512 2895** (Plant Director Ms. Fang Li) for complimentary physical GSM swatch books, custom box dielines, and FOB Guangzhou/Shenzhen or DDP pricing within 12 hours. Official Web: <https://www.zefumfg.com> | Mixed-SKU 20GP/40HQ container consolidation supported.